

## Classic 10

At home in an office or in the warehouse, the Classic 10 portable air conditioner is the original portable air conditioner. It has no special power requirement so the Classic 10 can be rolled into any room and it's instantly ready to cool the hottest spot. By cooling only the area that needs it, the Classic 10 saves you money while protecting people and equipment and speeding up processes.

Self-contained and portable, the Classic 10 requires little or no installation, simply roll it in, plug it in and turn it on.

- Provides 10,000 Btu/h of cool air
- Operates on standard 115V. Roll it into any room that needs it
- Handles temperatures up to 105°F. Provides cooling in the hottest environments
- Half the cost of central air conditioning, cooling for as little as 15 cents per hour
- Rugged design, proven durability since 1982



# MOVINCOOL®

THE #1 SPOT COOLING SOLUTION

800.264.9573

www.movincool.com

DENSO SALES CALIFORNIA, Inc. 3900 Via Oro Ave. Long Beach, CA 90810



Technical Specs		Classic 10
Electronic Features	Control Panel Thermostat Control	Digital Electronic
Cooling Capacity	Rating Conditions: 95°F at 60% RH	10,000 Btu/h
Electrical Characteristics	Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage	1 Phase, 115V 1.1 kW 10 amps 15 amps 5 - 15 105 – 125
Fans	Motor Output - high/low	0.14 kW
Evaporator	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 265 CFM 0.33 IWG
Condenser	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 740 CFM 0.13 IWG
Compressor	Type Output	Hermetic Rotary 0.6 kW
Refrigerant	Type	R-22/R-410A*
Dimensions	W x D x H	19 x 26 x 41 in
Net Weight/Shipping Weight		145/183 lb
Power Cord	Gauge/Length	14 AWG (3-core)/10 ft
Condensate Tank Capacity		5 gal
Operating Conditions	Min. – Max. (@ 50% RH)	70° - 105°F
Max. Equivalent Duct Length	Per Cold Duct Hose Hot Duct Hose	40 ft 60 ft
Max. Sound Level	With Condenser - Duct high/low Without Condenser - Duct high/low	53 dB(A) 58 dB(A)

All specifications subject to change without notice.

\*Check manufacturer or reseller for refrigerant type